

CABLE USB 2.0 STANDARD TIPO A M/TIPO B M



Supports data transmission rates up to 480 Mbit/s. Wire construction: AWG28 / AWG20. Shielded: Foil + 80% braiding. Plug moulded. Jacket: LSZH

Type of connector connection 1: USB-A
Number of poles connection 1: 4
Connection type connection 1: plug
Type of connector connection 2: USB-B
Number of poles connection 2: 4
Connection type connection 2: plug

TECHNICAL PARAMETERS

Article no.	Title	Colour	Length
CAB5219N.0,5	USB2.0 Connection Cable A-B, M-M, 0.5m, black, LSZH	black	0.5 m
CAB5219N.1	USB2.0 Connection Cable A-B, M-M, 1.0m, black, LSZH	black	1.0 m
CAB5219N.1,5	USB2.0 Connection Cable A-B, M-M, 1.0m, black, LSZH	black	1.5 m
CAB5219N.1,8	USB2.0 Connection Cable A-B, M-M, 1.8m, black, LSZH	black	1.8 m
CAB5219N.3	USB2.0 Connection Cable A-B, M-M, 3.0m, black, LSZH	black	3.0 m

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.

Article no.	Title	Colour	Length
CAB5219GR.0,5	USB2.0 Connection Cable A-B, M-M, 0.5m, black, LSZH	grey	0.5 m
CAB5219GR.1	USB2.0 Connection Cable A-B, M-M, 1.0m, black, LSZH	grey	1.0 m
CAB5219GR.1,5	USB2.0 Connection Cable A-B, M-M, 1.0m, black, LSZH	grey	1.5 m
CAB5219GR.1,8	USB2.0 Connection Cable A-B, M-M, 1.8m, black, LSZH	grey	1.8 m
CAB5219GR.3	USB2.0 Connection Cable A-B, M-M, 3.0m, black, LSZH	grey	3.0 m