

CABLE SVGA M/M ALTA CALIDAD CON FERRITA



Double shielded display cable specially capable against outer interference

75 Ohm, double-shielded, with 2 x ferrite cores

With thumb screws, moulded, black

Construction: 3 x coax RGB and 5 x control lines

Type of connector connection 1: HD-D-Sub

Number of poles connection 1: 15

Connection type connection 1: plug

Type of connector connection 2: HD-D-Sub

Number of poles connection 2: 15

Connection type connection 2: plug

TECHNICAL PARAMETERS

Article no.	Title	Colour	Length
CABV1.1,8	SVGA/HDTV Connection Cable, 2x HD-DSub 15, M-M, 1,8m, black	black	1.8 m
CABV1.3	SVGA/HDTV Connection Cable, 2x HD-DSub 15, M-M, 3,0m, black	black	3.0 m
CABV1.5	SVGA/HDTV Connection Cable, 2x HD-DSub 15, M-M, 5,0m, black	black	5.0 m
CABV1.10	SVGA/HDTV Connection Cable, 2x HD-DSub 15, M-M, 10,0m, black	black	10.0 m
CABV1.15	SVGA/HDTV Connection Cable, 2x HD-DSub 15, M-M, 15,0m, black	black	15.0 m
CABV1.20	SVGA/HDTV Connection Cable, 2x HD-DSub 15, M-M, 20,0m, black	black	20.0 m
CABV1.25	SVGA/HDTV Connection Cable, 2x HD-DSub 15, M-M, 25,0m, black	black	25.0 m

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.