


Latiguillo SFTP Cat. 6A LSZH

Ref.: MK6001.xxG



General data

The shielded Cat.6A RJ45 patch cable ensures excellent performance for **10 Gigabit** Ethernet applications. The moulded grommet captivates with its **slim design** and thus simplifies the insertion process in cramped conditions.

Cross section 4 x 2 x AWG27/7

Length imprint on boot

Available in **11 colours**

Allgemeine Daten

Connector type	RJ45 Standard green
Suitable for degree of protection (IP)	IP20
Cable type	S/FTP
Pin assignment	1:1
Locking lever	True
Colour anti-kink sleeve	grey
Fire retardant version	True
Model	Shielded
Jacket material	LSZH
UL approbated	False

Ref.: MK6001.xxG

Contacts	Gold plated
Allocation	acc. TIA/EIA 568B
Area of Application	Industrial Ethernet
Length imprint	True
Colour outer sheath	grey
Anti-kink sleeve	plugged in
Current capacity	max. 1 A
(Halogenfree)	True
Category	6A (TIA)

Mechanische Eigenschaften

Conductive shield	Selected shield contact
Mating cycles	2000
Bending radius	>30 mm

Kabelaufbau

Type of connector connection 2	RJ45 8(8)
AWG-size	27/7
Type of connector connection 1	RJ45 8(8)
Conductor Material	Copper
Raw cable	Cat.6A
Total screening	80 %
Cable construction	4x2

Kabelmantel

Low smoke	True
Printing	Cat.6A PATCH S/FTP 4x2xAWG27/7 LSZH ISO/IEC11801 ANSI/TIA-568-C.2 ***10Gigabit Ethernet***
Oil resistant (according to EN 60811-404)	False
Silicone-free	True
Flame-retardant	True
Outer diameter of the cable	6.0 mm
Halogen-free	True

Umgebungsbedingungen

Temperature range	-20 - 60 °C
-------------------	-------------

Ref.: MK6001.xxG

Elektrische Eigenschaften

Insulation resistance	10 MΩ
Loop resistance	370 Ω/km
Test voltage	1000 V DC, 1min
Impedance	100 ±15 Ω
Contact resistance	30 mΩ
NVP value	74 %
Conductor resistance DC	185 Ω/km
POE class	PoE+ acc. to IEEE802.3at
Resistance unbalance	3 %
Operating-/ tempering voltage	max. 50 V DC

Übertragungstechnische Eigenschaften

Transmission	10Gbit
Bandwidth	500MHz

Normen, Zulassungen, Zertifizierungen

Oil resistant (acc. EN 60811-2-1)	False
Connector	IEC 60603-7-51

MK6001.50G	RJ45 Patch cable S/FTP, Cat.6A, LSZH, 50m, grey	50.0 m	±5 %
------------	---	--------	------

Drawings

